

MULTI-ROW GEMSTONE BRACELET WITH 925 STERLING SILVER INSERT

By : Lucie T Perles&Co



Easy



0 minutes

How to make a 925 silver multirang bracelet for women with natural stones?

How to make a 925 silver women's multi-row bracelet with gemstones?

Tired of struggling every morning to put on all your bracelets but you absolutely want to have this accumulation effect on your wrist, ultra trendy? This tuto is made for you!

A unique bracelet with a single clasp that gives the impression of having 4 bracelets on your wrist! Here is the ideal combo, the 4-in-1 bracelet.

You will see how easy it is to create a multi-row bracelet with a 925 silver interlayer.

This DIY tutorial is suitable for beginners, you will only need a flat clip.

Discover our technical sheets to learn the basics of [jewellery creation](#).

Feel free to share the results of your bracelets by tagging us on Instagram or [on our](#) Facebook page.

Which material to use for Multi-row gemstone bracelet with 925 sterling silver insert?

SUPPLIES



925 Sterling Silver Spacer like faceted cabochon rond 2 loops 12mm x1
Ref. : ARG-685
Quantity : 1



Stringing wire color 7 strands 0.38mm x9,2m
Ref. : FC-724
Quantity : 1



Sterling Silver Lobster claw clasp 9mm
Ref. : FRM-060
Quantity : 1



925 Sterling Silver Crimp tubes 1.1x1 mm x100
Ref. : SL-448
Quantity : 1




6.4x0.8 mm 925 Sterling Silver Closed jump rings x10
Ref. : SL-460
Quantity : 1



Bead Faceted round beads 2mm Indian Agate x38cm
Ref. : SP-354
Quantity : 1



Bead Faceted round beads 2mm Howlite x38cm
Ref. : SP-355
Quantity : 1



Bead Gold stone beads imitation Sun stone 2 mm x38cm
Ref. : SP-363
Quantity : 1

steps

★ Step 1/2

Thread randomly the gemstone beads: howlite, indian agates and sun stone.

Do not hesitate to test on your wrist the rendering of the bracelet as you create it.

The total length of the bracelet should be about 68 cm for 4 turns. But you can make the bracelet longer to make 5 turns.

★ Step 2/2

Insert a bead to be crushed, then slide your clasp and iron your cabled wire in the bead to be crushed. Repeat the same operation on the other side with a closed ring.



Result

